



TOP 1 OIL PRODUCTS COMPANY

PRODUCT DATA SHEET

Revised: Sep. 2017

SUPER ATF

DESCRIPTION

SUPER AUTOMATIC TRANSMISSION FLUID (ATF) is a high performance, multipurpose automatic transmission fluid formulated to meet pre-2007 GM and Ford specifications. It is blended using prime base stocks and additives that provide oxidative and thermal stability, friction control, load carrying ability, corrosion and wear protection. SUPER ATF is specially formulated to prevent shudder and practically eliminates transmission overhauls due to sludge, corrosion and wear. It is an excellent choice in any transmission where the manufacturer recommends a DEXRON-III, MERCON, ALLISON C4, or Caterpillar TO-2 fluid, DENISON and VICKERS pumps.

FEATURES AND ADVANTAGES

- Excellent seal compatibility
- High resistance to oxidation
- Minimizes varnish and sludge formation
- No corrosion or rusting of parts
- Excellent for use as a power steering fluid
- Quiet performance
- Exceptional thermal stability
- Optimum friction characteristics
- Retains low temperature fluidity and high temperature stability

TYPICAL SPECS

API Gravity	33.0
Flash Point, °C	204
Pour Point, °C	-48
Viscosity:	
cP @ -40 °C, Brookfield	16500
cSt @ 40 °C	35.3
cSt @ 100°C	7.2
Viscosity Index	171
Color, D-1500	Red
Product Number:	
12x1 Quart	10392
1x18.95 Liters	10392-5
1x200 Liters	10392-7
12x1 Quart	13551
12x1 Liter	13553
4x5 Liters	13554

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

100 N. El Camino Real, San Mateo, CA, 94401, Tel: 650.347.3691 Fax: 650.340.8739 www.top1oil.com