



EVOLUTION MV ATF

DESCRIPTION

TOP 1 EVOLUTION MV ATF is a fully synthetic automatic transmission fluid blended with a specifically balanced additive combination that is manufactured to provide high oxidation stability, corrosion resistance, and wear protection. TOP 1 EVOLUTION MV ATF is a low viscosity multi-purpose fluid that meets and exceeds current original equipment manufacturers specifications for automatic transmission fluids, including some of the latest OEM specifications as specified

FEATURES AND ADVANTAGES

by GM, Ford, Chrysler, Toyota, Mitsubishi and others.

- Excellent wear protection and quiet, smooth operation
- Superior thermal and oxidation stability compared to conventional automatic transmission fluids
- Protects against rust and corrosion
- Outstanding seal compatibility
- Will not degrade nylon components

PERFORMANCE SPECIFICATIONS

TOP 1 EVOLUTION MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID (MV ATF) meets or exceeds the requirements of transmission manufacturers where the following ATF types are specified:

- Audi/VW: G-055-005-A2
- GM Dexron VI (backwards compatible to DII/IIIE/IIII/IIIG?IIIIH)
- Ford: M-LV, M-SP
- Hyundai/Kia: SP-IV
- Mitsubishi: Diaqueen ATF J-3
- Mercedes Benz: MB 236.12, MB 236.14*
- Nissan Matic S (backward compatible to Matic D/Matic J)
- Saab: 93 165 147
- Toyota/Lexus/Scion: WS
- OEMs: M1375.4

*Suitable For Use

TYPICAL SPECS

Gravity, °API	30.5
Pour Point, °C	-46
Viscosity:	
cSt @ 100°C	6.0 – 6.2
cP @ -40°C, Brookfield	7,900
Viscosity Index	> 145
Color	Red
Product Number:	
12x1 Liter	13363

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

100 N. El Camino Real, San Mateo, CA 94401, Tel: 650.347.3691 Fax: 650.340.8739 www.top1oil.com