



# TOP 1 OIL PRODUCTS COMPANY

## PRODUCT DATA SHEET

Revised: Sep. 2017

### MV ATF

#### DESCRIPTION

**TOP 1 MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID (MV ATF)** is a fully synthetic, high viscosity automatic transmission fluid formulated to meet Multi-Vehicle OEM specifications with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance. TOP 1 MV ATF is also compounded with a friction-modifying additive to provide smooth lock-up of clutches without chatter. TOP 1 MV ATF meets and exceeds current original equipment manufacturers specifications for automatic transmission fluids, including some of the latest OEM specifications as specified by GM, Ford, Chrysler, Toyota, Mitsubishi, and others.

#### FEATURES AND ADVANTAGES

- Excellent wear protection and quiet, smooth operation.
- Superior thermal and oxidation stability compared to conventional automatic transmission fluids.
- Outstanding seal compatibility and will not degrade nylon components.

#### PERFORMANCE SPECIFICATIONS

**TOP 1 MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID (MV ATF)** meets or exceeds the requirements of transmission manufacturers where the following ATF types are specified:

- ATF Type A-Suffix A / Allison C3, C4 (TES-228) & TES 295
- Aisin Warner A-1, 3309
- Audi ZF, 5HP19FL, 5HP24A, LT7114 & Audi/VW G-052-162-A1, G-052-162-A2, G-055-005-A2
- BMW ZF, 5HP18FL, 5HP24, 5HP30, LT 71141; Shell LA 2634; ETL-7045E; 8072B
- VW / Audi Part # G052 025(09M), G 052 990(09A), G 052025 A2
- Caterpillar Cat TO-2,
- Chrysler & American Motors ATF +3 / ATF +4
- Daewoo LT71141
- Esso LT 71141 Fiat (all vehicles),
- Ford M, MV, FNR5 (for Mazda), M2C138-CJ, M2C166H, MC2C924-A
- GM DII / II-E / III / IIIG / IIH / IIIG, GM 9986195, Strasbourg, 12378515 (Transynd)
- Hyundai / Kia SP-II, SP-III, SP-IV
- Honda ATF – Z1, DW-1 (except in CVTs)
- Idemitsu K17, Jatco 3100PL085 & Isuzu (all vehicles)
- JASO 1A (M315-2006)
- Jaguar M1375.4, ATF 3403 M115
- Jeep (ATF + 3, ATF + 4)
- JWS 3309
- Land Rover -Texaco N402,
- Mazda ATF M-III, M-V & Mini Cooper T-IV (except CVT)
- Mercedes ZF 4HP20, MB 236.1; 2; 3(PSF); 5(C-4); 6; 7; 8; 9; 10,
- MOPAR AS68RC ATF
- Nissan / Infiniti Matic D / J / K ,
- Peugeot ZF 4HP20 / Porsche ZF 5HP19FL, ATF 3403-M115, T-IV & Opel (all vehicles)
- Renault – all vehicles
- Saab 3309
- Subaru ATF, ATF-HP
- Shell 3403, 3353, LA2634
- Suzuki ATF 3317
- Texaco ETL-7045E, ETL-0872B, N402
- Toyota / Lexus / Scion Type T, T-II, T-III, T-IV (GM US PN 88900925), (GM Canada PN 22689186)
- Voith H55.6335.XX(G607), Turbo, ZF, Comat, ZF TE-ML 09/11, ZF TE-ML 03D,04D,09,ZF TE-ML 16L,17C
- Volvo 97340, 1161521, 1161540, T-IV, STD 1273.41

#### TYPICAL SPECS

Gravity, °API	35.3
Lbs/Gal	7.07
Sp. Gravity @ 15.6 / 15.6°C	0.848
Pour Point, °C	-40
Viscosity:	
cSt @ 100°C	7.3
cP @ -40°C, Brookfield	16,000
Viscosity Index	> 145
Color	Red
<b>Product Number:</b>	
12x1 Liter	13361

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

100 N. El Camino Real, San Mateo, CA 94401, Tel: 650.347.3691 Fax: 650.340.8739 www.top1oil.com