



**TOP 1 OIL PRODUCTS COMPANY**

**PRODUCT DATA SHEET**

Revised: Sep 2017

# LSD GEAR OIL 75W-90

## DESCRIPTION

**LSD GEAR OIL 75W-90** is a high quality, multipurpose gear lubricant designed for high performance automotive applications, specifically limited slip differentials. LSD GEAR OIL 75W-90 reduces wear and provides cleanliness in extreme conditions. This thermally stable gear lubricant is designed to operate and protect in both high and low extreme-temperature conditions.

## FEATURES AND ADVANTAGES

- API GL-5/MT-1
- Meets SAE J2360 (MiL-PRF-2105E) requirements
- Meets Mack GO-J and other European performance requirements
- Recommended for BMW final drives requiring limited-slip performance properties
- Recommended for GM, Ford, Chrysler, Mercedes, Mitsubishi, Volvo, Toyota
- Extreme-Pressure additives for wear protection

## TYPICAL SPECS

GRADE, SAE	ASTM TEST	75W-90
API Service Designation		GL-5/MT-1
Flash Point, °C	D-92	210
Pour Point, °C	D-97	-48
Viscosity:		
cSt @ 100°C	D-445	15
cP @ -40°C, Brookfield	D-2683	130,000
Viscosity Index	D-2270	145
Color	D-1500	2.0
<b>Product Number:</b>		
12x1 L		14391

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

100 N. El Camino Real, San Mateo, CA, 94401, Tel: 650.347.3691 Fax: 650.340.8739 [www.top1oil.com](http://www.top1oil.com)