



TOP 1 OIL PRODUCTS COMPANY

PRODUCT DATA SHEET

Revised: FEB. 2019

TRANSPORT

DESCRIPTION

TRANSPORT API CJ-4, CI-4, SL is a blend of premium syn-blend base oils and selected additives, designed to give excellent performance in all EGR engines. This engine oil contains an effective additive system which is compatible and keeps the EGR engines highly clean. It can be used for all new and old engines.

FEATURES AND ADVANTAGES

- Recommended for all engines using EGR or Naturally Aspirated Engines that specify CJ-4/CI-4/SL, & European and OEM claims
- Meets ACEA E3/ B3/ E2, MB 228.1/ 229.1, Volvo VDS, Cummins CES 20071/ 72/ 76/ 78, Mack EO-M & EO-M plus, Mack EO-N, DDC series 2000/ 4000 Category 1, Caterpillar ECF-1, MAN 271, MTU Type 1 specification
- Meets and exceeds EPA compliant engine requirements
- High TBN
- EGR compatible
- Backward compatible with old engines using different sulfur levels

TYPICAL SPECS

| GRADE, SAE | ASTM TEST | 10W-40 | 15W-40 |
|-------------------|-----------|--------------|--------------|
| API Gravity | D-287 | 31.3 | 31.5 |
| Flash Point, °C | D-92 | 220 | 221 |
| Pour Point, °C | D-97 | -25 | -25 |
| Viscosity: | | | |
| cSt @ 100°C | D-445 | 15.3 | 14.5 |
| CCS, cP | D-5293 | 6000 @ -25°C | 6000 @ -20°C |
| Viscosity Index | D-2270 | 134 | 140 |
| Color | | 2.0 | 2.0 |
| Sulfated Ash, wt% | D-874 | 1.2 | 1.2 |
| TBN | D-2896 | 10.5 | 10.5 |

Product Number:

| | | |
|-----------|-------|-------|
| 1x5 Gal | 17055 | 17045 |
| 1x53Gal | 17057 | 17047 |
| 1x330 Gal | | 17049 |

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

100 N. El Camino Real, San Mateo, CA, 94401, Tel: 650.347.3691 Fax: 650.340.8739 www.top1oil.com