



TOP 1 OIL PRODUCTS COMPANY

PRODUCT DATA SHEET

Revised: Sep. 2017

RG-80

DESCRIPTION

RG-80 is designed to protect, penetrate, loosen, clean rusted and corroded parts. It works into crevices, cracks, metal-to-metal joints leaving an oily film with high lubricity and corrosion inhibiting actions. Its deep penetrating action looses rust and carries lubricant into all internal surfaces. Contains no acid which would harm the basic metal or adjoining paint, plastic or wood.

FEATURES AND ADVANTAGES

Disassembling nuts, bolts, studs and pipe fittings removing gears and pulleys; pressing off bearing, freeing stuck valves and frozen bearings; loosening up roller chains and conveyor belt drives, disassembling machinery.

- Penetrated and works on contract
- Loosens rusted and corroded parts
- Clean removes light rust
- Save time and labor costs
- Contain corrosion inhibitor
- Protect metals and parts

TYPICAL SPECS

Physical state	Pressurized Liquid
Odor	Mild
Color	Light Brown
pH	6 - 8
Boiling point	>160°C
Melting point	Not Applicable
Flash point and method	80°C/C.C
Solubility in water	Negligible
Evaporation rate	Not Available
Specific gravity	0.89 gr/cm ³ @ 20°C
Product Number: 12x350 ML	90150

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

851 Burlway Rd., Ste 600, Burlingame, CA 94010, Tel: 650.347.3691 Fax: 650.340.8739 www.top1oil.com