



**TOP 1 OIL PRODUCTS COMPANY**

**PRODUCT DATA SHEET**

Revised: Aug 2020

# MP GEAR OIL

## DESCRIPTION

**MULTI-PURPOSE (MP) GEAR OILS** are thermally stable, extreme pressure, multi-purpose gear lubricants formulated to withstand the most severe conditions including extreme temperatures and high load conditions. These long-life gear oils exceed API service classification GL-5/GL-4\*/MT-1. MP GEAR OILS are manufactured from the highest quality base oils fortified with VI improvers, rust inhibitors, foam suppressants, anti-wear, and extreme pressure additives and pour point depressants. These multi-viscosity grades may be used over wide temperature ranges.

## FEATURES AND ADVANTAGES

- Exceeds API GL-5
- Meets API GL-4 (\*For Manual Transmissions Only)
- SAE J2360
- Mack Specification GO-J
- Exceptional thermal and oxidation stability
- All-weather protection
- Long lubricant life
- Protects hypoid gears from wear and scuffing
- Multi-viscosity provides year round use
- Compatible with other automotive gear oils

## TYPICAL SPECS

GRADE, SAE	80W-90	85W-140
Gravity, °API	26.0	24.5
Flash Point, °C	213	221
Pour Point, °C	-32	-15
Viscosity @ 40°C, cSt	172	347
Viscosity @ 100°C, cSt	16.3	25.5
Viscosity Index	98	96
Color, D1500	5.5	7.0
Brookfield, cPs (-26°C)	90,000	
Brookfield, cPs (-12°C)		85,000
<b>Product Number:</b>		
1x18.95 L (5 Gal)	10355	10345
1x208 L (55 Gal)	10357-55	10347-55

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

100 N. El Camino Real, San Mateo, CA, 94401, Tel: 650.347.3691 Fax: 650.340.8739 [www.top1oil.com](http://www.top1oil.com)