



# PRODUCT DATA SHEET

## HD PLUS 10W-30

### Description

TOP 1 HD PLUS 10W-30 Synthetic Blend Engine Oil is a superior quality oil formulated with premium quality base oils and additives. HD PLUS 10W-30 is formulated to reduce engine wear and friction while preventing oxidation.

Exceeds API CI-4, CH-4, CG-4, CF-4/SL, SJ

### Features & Advantages

Designed for Common Rail Engines

Reduces Engine Wear

Reduces Friction

Prevents Oxidation

With Regular Use, HD PLUS 10W-30 Keeps Engine Clean and Extends Engine Life

### Typical Characteristics

Name, units	Test Method	HD PLUS 10W-30
Viscosity, Kinematic cSt @ 100 °C	ASTM D445	10.5
Viscosity @ -25°C (CCS), cP	ASTM D5293	6000
Viscosity Index	ASTM D2270	145
Flash Point (COC), °C	ASTM D92	227
Pour Point, °C	ASTM D97	-30
Gravity, °API	ASTM D287	31.5
TBN, mgKOH/g	ASTM D2896	9.2
Sulfated Ash, wt%	ASTM D874	1.2
Appearance	Visual	Bright & Clear
Product Number 4 x 5 L 1 x 208 L (55 G)		17684 17687