## **ACTION MATIC**

Revised: Sep 2017

## DESCRIPTION

**ACTION MATIC** is a 4T high performance oil designed to meet the latest motorcycle manufacturers warranty requirements. Specifically formulated to meet the demands of the small displacement high RPM fuel efficient engines found in today's domestic and foreign motorcycles. These engines experience higher operating temperatures and require a motor oil which offers maximum protection against both viscosity and thermal breakdown.

The oil is a blend of Synthetic / Hydrocraked premium base oils and special additives which protects against high temperature oxidation, wear, and viscosity breakdown. It is fortified with detergent-dispersants and rust and corrosion inhibitors to keep engines exceptionally clean and free of sludge, varnish and rust.

It meets the performance of API SJ, JASO MB specification. The product is specially designed for "Dry" clutch systems.

## FEATURES AND ADVANTAGES

- •Meets and exceeds OEMs warranty requirements.
- · Highly oxidation stable protects engine from oil thickening, high temperature sludge and varnish deposits.
- Effective detergent-dispersants keeps engine parts clean.
- High TBN/alkaline reserve effectively neutralizes corrosive acids formed by combustion to protect critical turbo bearings and other vital engine surfaces.
- · Anti-wear agents effectively protect cam lobes and other highly loaded parts from wear.
- Exceeds API Service Classification of API SJ/CD, JASO MB requirements.
- Recommended for "dry" types of Motorcycles.

## TYPICAL SPECS

GRADE, SAE	ASTM TEST	20W40	10W30	10W40
API Gravity	D-287	33.5	33.0	32.0
Flash Point, °F	D-92	420	420	430
Pour Point, °C	D-97	-25	-35	-35
Viscosity:				
cST @ 100°C	D-445	14.0	13.5	14.0
CCS @ -25°C	D-5293	8000	6000	6,000
Appearance	Visual	Bright & Clear	Bright & Clear	Bright & Clear
Color	D-1500	3.0	3.0	4.0
Zinc, wt%		0.13	0.12	0.13
TBN	D-2896	6.2	6.2	6.0
Product Number:				
12x800 cc		10799	10798	19032
12x1 L (Can)				19038
12x1 L (Bottle)		19901		19031