

## ХМ

## DESCRIPTION

**XM** is a 4T conventional performance oil designed to meet the latest motorcycle manufacturers warranty requirements. Specifically formulated to meet the demands of the small displacement high RPM fuel efficient engines found in today's domestic and foreign motorcycles. These engines experience higher operating temperatures and require a motor oil which offers maximum protection against both viscosity and thermal breakdown.

The oil is a blend of premium conventional base oils and special additives which protects against high temperature oxidation, wear, and viscosity breakdown. It is fortified with detergent-dispersants and rust and corrosion inhibitors to keep engines exceptionally clean and free of sludge, varnish and rust.

It meets the performance of API SJ, JASO MA2 specification

## FEATURES AND ADVANTAGES

•SAE 20W50 meets and exceeds OEMs warranty requirements.

• Highly oxidation stable - protects engine from oil thickening, high temperature sludge and varnish deposits.

• Effective detergent-dispersants keeps engine parts clean.

• High TBN/alkaline reserve effectively neutralizes corrosive acids formed by combustion to protect critical turbo bearings and other vital engine surfaces.

•Anti-wear agents effectively protect cam lobes and other highly loaded parts from wear.

•XM 20W50 Oil exceeds API Service Classification of API SJ, JASO MA2 requirements.

·Recommended for all types of Motor Cycles.

TYPICAL	SPECS	

<b>GRADE, SAE</b> API Gravity Flash Point, °F Pour Point, °C Viscosity:	<b>ASTM TEST</b> D-287 D-92 D-97	<b>20W50</b> 32.50 >420 -20
cST @ 100°C CCS @ -25°C Viscosity Index Appearance Color Calcium, wt% Magnesium, wt% Phosphorus, wt% Zinc, wt%	D-445 D-5293 D-2270 Visual D-1500	20.5 5000 155 Bright & Clear 3.0
Sulfated Ash, wt% TBN <b>Product Number:</b> 12x1 Liter 1x53 Gal 1x330 Gal	D-874 D-2896	0.99 7.3 19811 19817 19819