

# PRODUCT DATA SHEET

## XLR CONVENTIONAL 25W-60

### Description

TOP 1 XLR CONVENTIONAL 25W-60 API CF-4 Heavy Duty Engine Oil is a superior quality mineral oil formulated for higher mileage heavy duty vehicles. XLR 25W-60 is especially effective in protecting engines against excessive oil consumption while reducing wear and friction.

Exceeds API CF-4

### Features & Advantages

Reduces Oil Consumption

Reduces Friction

Reduces Engine Wear

With Regular Use, XLR 25W-60 Keeps Engine Clean and Extends Engine Life

### Typical Characteristics

Name, units	Test Method	XLR CONVENTIONAL 25W-60
Viscosity, Kinematic cSt @ 100 °C	ASTM D445	22.0
Viscosity @ -10°C (CCS), cP	ASTM D5293	10000
Viscosity Index	ASTM D2270	160
Flash Point (COC), °C	ASTM D92	215
Pour Point, °C	ASTM D97	-20
Gravity, °API	ASTM D287	30.0
TBN, mgKOH/g	ASTM D2896	9.5
Sulfated Ash, wt%	ASTM D874	1.3
Appearance	Visual	Bright & Clear
Product Number 4 x 5 L 1 x 18.9 L (5 G) 1 x 208 L (55 G)		12604 12605 12607

**GO SYNTHETIC**