

PRODUCT DATA SHEET

ACTION 20W-50

Description

TOP 1 ACTION 20W-50 Synthetic Blend Motorcycle Oil is designed to meet the needs of the most advanced 4T motorcycles. ACTION contains proprietary additives which provide greater performance and protection. It provides maximum protection against thermal and viscosity breakdown, cylinder scuffing, and high temperature deposit formation, resulting in consistent lubrication and higher oil film strength for longer engine life.

Meets JASO MA2 and API SP

Features & Advantages

Increased Oxidation Stability

Increased Wear Protection

Triple Protection of Engine, Clutch and Gears

Typical Characteristics

Name, units	Test Method	ACTION 20W-50
Viscosity, Kinematic cSt @ 100 °C	ASTM D445	20.5
Viscosity @ -15°C (CCS), cP	ASTM D5293	5000
Viscosity Index	ASTM D2270	155
Flash Point (COC), °C	ASTM D92	> 216
Pour Point, °C	ASTM D97	-20
TBN, mgKOH/g	ASTM D2896	7.3
Gravity, °API	ASTM D287	32.5
Sulfated Ash, wt%	ASTM D874	0.99
Appearance	Visual	Bright & Clear
Product Number 12 x 1 L 1 x 60 L		19911 19918

GO SYNTHETIC