

PRODUCT DATA SHEET

HD SPORT 15W-40

Description

TOP 1 HD SPORT 15W-40 Synthetic Diesel Engine Oil is a superior quality oil that is formulated to provide greater protection than a standard 15W-40. TOP 1 HD SPORT is formulated for engines operating under severe service and a wide range of climate conditions. It is suitable for virtually all modern low-emission heavy duty engines.

Meets API CI-4/CH-4, ACEA E7-08 Issue 2/E7-12

Features & Advantages

Extra Protection Against Corrosion

Extra High Purity

Extra Wear Control

Extra Soot Dispersion

Extra Low Volatility

Typical Characteristics

Name, units	Test Method	HD SPORT 15W-40
Viscosity, Kinematic cSt @ 40°C cSt @ 100°C	ASTM D445	109.57 14.92
Viscosity @ low temp (CCS), cP	ASTM D5293	4977
Viscosity @ hi temp (HTHS), cP	ASTM 4683	5.27
Viscosity Index	ASTM D2270	142
Flash Point (COC), °C	ASTM D92	216
Pour Point , °C	ASTM D97	-33
TBN , mgKOH/g	ASTM D2896	11.57
Density @ 15°C , kg/m ³	ASTM D4052	856.9
Appearance	Visual	Green
Product Number 12 x 1 L 4 x 5 L		92641 92644

GO SYNTHETIC