

PRODUCT DATA SHEET

HD 15W-40

Description

TOP 1 HD Diesel 15W-40 Synthetic Blend Engine Oil is a superior quality diesel oil formulated with premium quality base oils and additives. HD 15W-40 is formulated to reduce engine wear and friction while preventing oxidation.

Exceeds API CI-4/SL. Suitable for all low emission Heavy Duty engines especially those with exhaust after treatment devices.

Features & Advantages

Reduces Engine Wear

Reduces Friction

Prevents Oxidation

With Regular Use, HD 15W-40 Keeps Engine Clean and Extends Engine Life

Typical Characteristics

Name, units	Test Method	HD 15W-40
Viscosity, Kinematic cSt @ 100°C	ASTM D445	15.61
Viscosity, Kinematic cSt @ 40°C	ASTM D445	110.1
Viscosity @ -20°C (CCS), cP	ASTM D5293	3364
Viscosity Index	ASTM D2270	150
Flash Point (COC), °C	ASTM D92	238
Pour Point, °C	ASTM D97	-39
Density @ 15°C, kg/m³	ASTM D4052	864.8
TBN, mgKOH/g	ASTM D2896	11.4
Humidity, %	ASTM D2247	trace
Sulfated Ash, wt%	ASTM D874	1.64

GO SYNTHETIC