

PRODUCT DATA SHEET

CVT

Description

TOP 1 CVT Fluid is formulated to provide high oxidation stability, heat resistance, and wear protection. TOP 1 CVT Fluid is a multi-purpose CVT fluid that meets and exceeds all current original equipment manufacturers specifications for continuously variable transmission fluids, including some of the latest OEM specifications as specified by Audi, Mitsubishi, Nissan, Saturn, Subaru and Toyota.

Applications

- DAIHATSU (AMIX CVTF-DC/DFE, FLUID TC)
- HONDA (MULTIMATIC FLUID (HMMF), HCF-2)
- HYUNDAI/KIA (SP-CVT-1)
- MAZDA (CVTF3320)
- MERCEDES BENZ (CVT28/MB 236.20)
- MITSUBISHI (DIAQUEEN CVTF-J1, DIAQUEEN CVTF-J4)
- SUBARU (I-CVTF, LIEARTRONIC CVTF, K0425Y0710, CV-30, E-CVTF)
- TOYOTA (FLUID TC, FLUID FE)
- VW (TL 52180, G 052 180 A2, G052 516)

Typical Characteristics

Name, units	Test Method	CVT
Viscosity, Kinematic cSt @ 100°C	ASTM D445	7.357
Viscosity, Kinematic cSt @ 40°C	ASTM D445	32.09
Viscosity @ -40°C (Brookfield), cP	ASTM D2983	6560
Viscosity Index	ASTM D2270	206
Flash Point (COC), °C	ASTM D92	218
Pour Point, °C	ASTM D97	-48