

PRODUCT DATA SHEET

EVOLUTION MV ATF

Description

TOP 1 EVOLUTION MV ATF is manufactured to provide high oxidation stability, corrosion resistance, and wear protection. TOP 1 EVOLUTION MV ATF is a low viscosity multi-purpose fluid that meets and exceeds current original equipment manufacturers specifications for automatic transmission fluids.

Features & Advantages

- Excellent wear protection and quiet, smooth operation
- Superior thermal and oxidation stability
- Protects against rust and corrosion
- Will not degrade nylon components

Applications

- AUDI/VW (Audi/VW: G-055-005-A2, G-055-162-A2/A6, G-060-162-A1/A2/A6)
- BMW (PN 83220142516, 83220397114, 83222152426, 163514)
- FORD (MERCON LV-FF-WSS-M2C-938A/SF, XT-10 QLV)
- GM (DEXRON IV-BACKWARD COMPATIBLE TO DEXRON II//IID//IIE//IIG//IIH)
- HYUNDAI/KIA (NWS-9638 T-5, PN 040000C90SG, SPH-IV)
- MERCEDES-BENZ (MB 236-12, MB 236-14/15/41)
- MITSUBISHI (DIAQUEEN J3)
- NISSAN (MATIC S FLUID (BACKWARD COMPATIBLE TO MATIC D/MATIC J))
- SAAB (93 165 147)
- TOYOTA/LEXUS (ATFWS)
- JASO (M315-2013 1A-LV)
- OEMs: M1375.4

Typical Characteristics

Name, units	Test Method	EVOLUTION MV ATF
Viscosity, Kinematic cSt @ 100°C	ASTM D445	6.168
Viscosity, Kinematic cSt @ 40°C	ASTM D445	25.69
Viscosity @ -40°C (Brookfield), cP	ASTM D2983	18700
Viscosity Index	ASTM D2270	204
Pour Point, °C	ASTM D97	-48