

PRODUCT DATA SHEET

XM-88 10W-40

Description

TOP 1 XM-88 10W-40 Fully Synthetic Motorcycle Oil is designed to meet the needs of the most advanced 4T motorcycles. XM-88 10W-40 is specially formulated to enhance engine performance while maximizing fuel economy.

Meets JASO MA2 and API SP

Features & Advantages

Increased Oxidation Stability

Increased Wear Protection

Triple Protection of Engine, Clutch and Gears

Typical Characteristics

Name, units	Test Method	XM-88 10W-40
Viscosity, Kinematic cSt @ 100 °C	ASTM D445	14.1
Viscosity @ -25°C (CCS), cP	ASTM D5293	3841
Flash Point (COC), °C	ASTM D92	246
Pour Point, °C	ASTM D97	-36
TBN, mgKOH/g	ASTM D2896	6.9
Density @ 15°C, kg/m ³	ASTM D4052	841.2
Product Number 12 x 1 L 1 x 275 G		19838 19839

PRODUCT DATA SHEET

XM-88 15W-50

Description

TOP 1 XM-88 15W-50 Fully Synthetic Motorcycle Oil is designed to meet the needs of the most advanced 4T motorcycles. XM-88 15W-50 is specially formulated to enhance engine performance while maximizing fuel economy.

Meets JASO MA2 and API SP

Features & Advantages

Increased Oxidation Stability

Increased Wear Protection

Triple Protection of Engine, Clutch and Gears

Typical Characteristics

Name, units	Test Method	XM-88 15W-50
Viscosity, Kinematic cSt @ 100 °C	ASTM D445	18.6
Viscosity @ -20°C (CCS), cP	ASTM D5293	3017
Flash Point (COC), °C	ASTM D92	250
Pour Point, °C	ASTM D97	-36
TBN, mgKOH/g	ASTM D2896	6.9
Density @ 15°C, kg/m ³	ASTM D4052	841.2
Product Number 12 x 1 L 1 x 275 G		19868 19869